

















PU		
	1.5mm	2.0mm
	2m x 27.5m = 55m ²	2m x 20m = 40m ²
	2360g/m ²	3200g/m ²
	GENERAL PERFORMANCE EN 649 ASTM F1913	
	REACTION TO FIRE UIC 564-2: 1991 Conforms ISO 3795 0mm/mn EN 13501-1 Class Bfl-S1 ASTM E662 <450	
	95/28/EC Conforms BS 6853: 1999 Class 1b † EN ISO 9239-1 ≥8kw/m ² EN ISO 11925-2 Pass ASTM E648 Class 1 †2.0mm	
	SLIP RESISTANCE EN 13893 Class DS AS/NZS 4586 R9	
	ABRASION RESISTANCE EN 649 Group M	
	STATIC LOAD LIMIT ASTM F970 750 psi (modified)	
	MARITIME USAGE American Bureau of Shipping† US Coast Guard† Marine Equipment Directive† 96/98/EC SOLAS 74 China Classification Society Approved† ClassNK Approved† †2.0mm	
	 MED CERTIFIED BY 0062	
	ENVIRONMENT Voyager PU is 100% recyclable and contains 25% recycled material.	
	LIGHT FASTNESS ISO 105-B02 Method 3 ≥6	
	For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Voyager. At the date of issue the data presented is correct. However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.	
		
POLYFLOR LTD. - TRANSPORT FLOORING DIVISION PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK TEL: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 2515 E-MAIL: TRANSPORT@POLYFLOR.COM WWW.VOYAGER.POLYFLOR.COM		
		 FLOORING  2006