

VOYAGER PUR



PUR



2.0mm



2m x 20m = 40m²



3550g/m²



GENERAL PERFORMANCE

EN 649
ASTM F1913



REACTION TO FIRE

UIC 564-2: 1991 Conforms
ISO 3795 Omm/mn
EN 13501-1 Class Bfl-S1

95/28/EC Conforms
BS 6853: 1999 Class 1b

EN ISO 9239-1 ≥8kw/m²
EN ISO 11925-2 Pass

ASTM E648 Class 1



SLIP RESISTANCE

EN 13893 Class DS
AS/NZS 4586 R9



ABRASION RESISTANCE

EN 649 Group M



STATIC LOAD LIMIT

ASTM F970 750 psi (modified)



MARITIME USAGE

American Bureau of Shipping
US Coast Guard
Marine Equipment Directive
96/98/EC
SOLAS 74
China Classification Society Approved
ClassNK Approved



ENVIRONMENT

Voyager PUR is 100% recyclable and contains 25% recycled material.



LIGHT FASTNESS

ISO 105-B02 Method 3 ≥6



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Voyager.
At the date of issue the data presented is correct.
However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.



POLYFLOR LTD. - TRANSPORT FLOORING DIVISION

PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 2515
E-MAIL: TRANSPORT@POLYFLOR.COM
WWW.VOYAGER.POLYFLOR.COM

James Holstead™
FLOORING

