## voyager maritime PU

A design-led collection of Luxury Vinyl Tiles, authentically representing natural materials such as wood, stone and slate. Each product features realistic surface textures and a polyurethane treatment.

Ideally suited to all front of house, heavy footfall on board areas.

		2.0mm 0.55mm
		0.55mm
		18 @ 305 x 610mm = 3.34m <sup>2</sup> 36 @ 102 x 914mm = 3.34m <sup>2</sup> 18 @ 152 x 1219mm = 3.34m <sup>2</sup> 15 @ 184 x 1219mm = 3.37m <sup>2</sup> 14 @ 203 x 1219mm = 3.46m <sup>2</sup>
		3520g/m²
EN 649/EN ISO 10582 MED 96/98 EC		Conforms Conforms
EN 13501-1 IMO MSC 307(88) Annex 1 Part 2 and 5	B <sub>II</sub> -s1	Class BfI-S1 Pass
EN 13893 DIN 51130	DS	Class DS R10 For safety flooring with sustainable wet slip resistance, refer to Voyager MarineSafe
EN 649 / EN ISO 10582		Group T / Type 1
Flooring		100% recyclable, 25% recycled material
US Coast Guard Marine Equipment Directive 96/98/EC SOLAS 74 Class NK		Conforms Conforms Approved
t	Pu	Polyurethane surface treatment
EN 433 / EN ISO 24343-1	٠	≤ 0.1mm
EN 434 / EN ISO 23999	(K Z)	≤ 0.25% max
ISO 105-B02 Method 3	<b>%</b>	≥ 6
		For information regarding handling and installation, adhesives, maintenance, and applications, consult Polyflor Technical Support on +44 (0)161 767 1912.  VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.
N EII EC F LNSC t	MED 96/98 EC EN 13501-1 MO MSC 307(88) Annex 1 Part 2 and 5 EN 13893 DIN 51130 EN 649 / EN ISO 10582 Flooring US Coast Guard Marine Equipment Directive 96/98/EC SOLAS 74 Class NK EN 433 / EN ISO 24343-1 EN 434 / EN ISO 23999	EN 649/EN ISO 10582 MED 96/98 EC  EN 13501-1 MO MSC 307(88) Annex 1 Part 2 and 5  EN 13893 DIN 51130  EN 649 / EN ISO 10582  Flooring  JS Coast Guard Marine Equipment Directive 96/98/EC SOLAS 74 Class NK  EN 433 / EN ISO 24343-1  EN 434 / EN ISO 23999

The data presented is correct at the time of printing.

WWW.VOYAGER.POLYFLOR.COM

March 2016

FLOORING

