













# voyager PUR transport flooring

VOYAGER<sup>TM</sup> PUR

## voyager PUR

Heavy-duty floorcovering with a polyurethane reinforcement for low cost, lifelong polish free maintenance. Suitable for road, marine and certain rail applications.

Gauge	ISO 24346 (EN 428)		2.0mm
Roll Length	ISO 24341 (EN 426)		2m x 20m = 40m <sup>2</sup>
Product Weight	ISO 23997 (EN 430)		3550g/m <sup>2</sup>
General Performance	ISO 10581 (EN 649) ASTM F1913		Conforms Conforms
Reaction to Fire	IMO MSC 307 (88) Annex 1 Part 2 and 5 EN 13501-1 ASTM E648		Pass Class Bfl-S1 Class 1
Slip Resistance	EN 13893 DIN 51130 / DIN EN 16165 Ann. B		Class DS R9
Binder Content	ISO 10581		Type II
Environment			100% recyclable and contains 25% recycled material
Marine Usage	American Bureau of Shipping Marine Equipment Directive 2014/90/EU SOLAS 74 China Classification Society Class NK		Conforms Conforms Conforms Approved Approved
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970		≤0.10mm ≤0.125mm (750psi)
Dimensional Stability	ISO 23999 (EN 434)		≤0.4% max
Light Fastness	ISO 105-B02 Method 3		≥6
Notes			For information regarding handling and installation, adhesives, maintenance, and applications, consult Polyflor.



May 2022 V008/6

The data presented is correct at the time of printing.  
L'information présentée est valable au date d'imprimer.  
Sie geben nur einen kleinen Teil des gesamten Dekors und der Farbe wieder.  
Los datos presentados eran correctos en el momento de su impresión.

