












voyager PUR
transport flooring

VOYAGERTM PUR

voyager PUR

Heavy-duty floorcovering with a polyurethane reinforcement for low cost, lifelong polish free maintenance. Suitable for road, marine and certain rail applications.

Gauge			2.0mm
Roll Length			2m x 20m = 40m ²
Product Weight			3550g/m ²
General Performance	EN 649 / EN ISO 10581 ASTM F1913		Conforms Conforms
Reaction to Fire	UN ECE 118.02 EN 13501-1 ASTM E662 ASTM E648 IMO MSC 307 (88) Annex 1 Part 2 and 5		Complies Class Bfl-S1 <450 Class 1 Pass
Slip Resistance	EN 13893 DIN 51130		Class DS R9
Abrasion Resistance	EN 660-2		Group M
Binder Content	EN ISO 10581		Type II
Environment			100% recyclable and contains 25% recycled material
Marine Usage	American Bureau of Shipping US Coast Guard Marine Equipment Directive 2014/90/EU SOLAS 74 China Classification Society Class NK Bureau Veritas (MED) DNV GL Russian Maritime		Approved Conforms Conforms Conforms Approved Approved Approved Approved Approved
VOC Emissions	Finnish M1 Classification		Certified
Maintenance Enhancement			Polyurethane reinforcement
Residual Indentation	EN 433 / EN ISO 24343-1 ASTM F970		≤0.1mm 750 psi (modified)
Dimensional Stability	EN 434 / EN ISO 23999		≤0.4%
Light Fastness	ISO 105-B02 Method 3		≥6
Notes			For information regarding handling and installation, adhesives, maintenance, and applications, consult Polyflor.

