

voyager XL

Heavy-duty, homogeneous flooring with a marbled decoration. Voyager XL is recommended for use where long life under heavy traffic is required. Suitable for road, marine and certain rail applications.

Gauge	ISO 24346 (EN 428)		1.5mm 2.0mm
Roll Size	ISO 24341 (EN 426)		1.5mm: 2m x 27.5m = 55m ² 2.0mm: 2m x 20m = 40m ²
Total Weight	ISO 23997 (EN 430)		1.5mm: 2360g/m ² 2.0mm: 3200g/m ²
General Performance	ISO 10581 (EN 649) ASTM F1913		Conforms Conforms
Reaction to Fire	IMO MSC 307(88) Annex 1 Part 2 and 5 EN 13501-1 ASTM E662 ASTM E648		Pass (2.0mm) Class Bfl-S1 <450 Class 1
Slip Resistance	EN 13893 AS/NZS 4586		Class DS R9
Abrasion Resistance	EN 660-2		Group M
Binder Content	ISO 10581		Type II
Sustainability			100% recyclable and contains 25% recycled material
Marine Usage	American Bureau of Shipping Marine Equipment Directive 2014/90/EU SOLAS 74 China Classification Society Class NK		Approved (2.0mm) Conforms (2.0mm) Conforms (2.0mm) Conforms (2.0mm) Conforms (2.0mm)
Residual Indentation	ISO 24343-1 (EN 433) ASTM F970		≤0.10mm <0.125mm (750 psi)
Dimensional Stability	ISO 23999 (EN 434)		≤0.40%
Light Fastness	ISO 105-B02 Method 3		≥6
Notes			For information regarding handling and installation, adhesives, maintenance and applications, consult Polyflor.

Oct 2024 V013/1

Decoration and shade may vary slightly from the samples shown.
The data presented is correct at the time of printing.
L'information présentée est valable au date d'imprimer.
Sie geben nur einen kleinen Teil des gesamten Dekors und der Farbe wieder.
Los datos presentados eran correctos en el momento de su impresión.

voyager XL



8740Δ
NCS S 0804-Y70R

w/r 9520
LRV 75



8640 Δ
NCS S 8502-R

w/r 8640
LRV 6



9010
NCS S 3005-Y50R

w/r 9010
LRV 40



9340*
NCS S 2002-Y50R

w/r 9340
LRV 54



9200*
NCS S 4000-N

w/r 9200
LRV 32



9180
NCS S 3020-Y10R

w/r 9180
LRV 37



9110
NCS S 3010-Y30R

w/r 9110
LRV 40



9120*
NCS S 4502-G

w/r 9120
LRV 28



9190
NCS S 3005-G20Y

w/r 9190
LRV 38



8580
NCS S 5030-R

w/r 8580
LRV 9



9040
NCS S 4030-B10G

w/r 9040
LRV 19



9170
NCS S 4020-R90B

w/r 9170
LRV 23

* Also available in 1.5mm sheet

Δ 8740 & 8640 feature a marbled decoration. They are not plain in terms of appearance.

w/r = weld rod NCS = Natural Colour System LRV = Light Reflectance Value



100% RECYCLABLE
CONTAINS 25% RECYCLED MATERIAL

