

# VOYAGER XL

**XL**



1.5mm

2.0mm



2m x 27.5m = 55m<sup>2</sup>

2m x 20m = 40m<sup>2</sup>



2360g/m<sup>2</sup>

3200g/m<sup>2</sup>



**GENERAL PERFORMANCE**

EN 649  
ASTM F1913



**REACTION TO FIRE**

UIC 564-2: 1991 Conforms  
ISO 3795 0mm/mn  
EN 13501-1 Class Bfl-S1

95/28/EC Conforms  
BS 6853: 1999 Class 1b<sup>†</sup>

EN ISO 9239-1 ≥8kw/m<sup>2</sup>  
EN ISO 11925-2 Pass

ASTM E662 <450  
ASTM E648 Class 1

†2.0mm



**SLIP RESISTANCE**

EN 13893 Class DS  
AS/NZS 4586 R9



**ABRASION RESISTANCE**

EN 649 Group M



**STATIC LOAD LIMIT**

ASTM F970 750 psi (modified)



**MARITIME USAGE**

American Bureau of Shipping<sup>†</sup>  
US Coast Guard<sup>†</sup>  
Marine Equipment Directive<sup>†</sup>  
96/98/EC  
SOLAS 74  
China Classification Society Approved<sup>†</sup>  
ClassNK Approved<sup>†</sup>

†2.0mm



**ENVIRONMENT**

Voyager XL is 100% recyclable and contains 25% recycled material.



**LIGHT FASTNESS**

ISO 105-B02 Method 3 ≥6



For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor Voyager.  
At the date of issue the data presented is correct.  
However, Polyflor Ltd. reserve the right to make changes which do not adversely affect performance or quality.

