

















# voyager maritime PU

A design-led collection of Luxury Vinyl Tiles, authentically representing natural materials such as wood, stone and slate. Each product features realistic surface textures and a polyurethane treatment. Ideally suited to all front of house, heavy footfall on board areas.

Gauge		2.0mm	
Wearlayer		0.55mm	
Tiles Size Plank Sizes		18 @ 305 x 610mm = 3.34m <sup>2</sup> 36 @ 102 x 914mm = 3.34m <sup>2</sup> 18 @ 152 x 1219mm = 3.34m <sup>2</sup> 15 @ 184 x 1219mm = 3.37m <sup>2</sup> 14 @ 203 x 1219mm = 3.46m <sup>2</sup>	
Product Weight		3520g/m <sup>2</sup>	
General Performance	EN 649/EN ISO 10582		Conforms 
Reaction to Fire	IMO MSC 307(88) Annex 1 Part 2 and 5		Pass
Slip Resistance	EN 13893 DIN 51130		Class DS R10 For safety flooring with sustainable wet slip resistance, refer to Voyager MarineSafe
Abrasion Resistance	EN 649 / EN ISO 10582		Group T / Type 1
Environmental Preferable Flooring			100% recyclable, 25% recycled material
Marine Usage	US Coast Guard Marine Equipment Directive 2014/90/EU SOLAS 74 Class NK		Conforms Conforms Conforms Approved
Maintenance Enhancement			Polyurethane surface treatment
Indentation-Residual	EN 433 / EN ISO 24343-1		≤ 0.1mm
Dimensional Stability	EN 434 / EN ISO 23999		≤ 0.25% max
Light Fastness	ISO 105-B02 Method 3		≥ 6
Notes			For information regarding handling and installation, adhesives, maintenance, and applications, consult Polyflor Technical Support on +44 (0)161 767 1912.  VARIATION IN COLOUR AND DESIGN IS A FEATURE OF THESE PRODUCTS INTENDED TO ENHANCE THE NATURAL APPEARANCE OF THE FLOOR.



The data presented is correct at the time of printing.

Sept 2021