














voyager polysafe stud tile

Heavy contract, synthetic rubber floor tile with low profile studded surface. Voyager Polysafe Stud Tile is suitable for use in heavily trafficked areas such as corridors, shops, bars, restaurants, leisure areas, crew areas and technical areas.

Gauge		3.0mm	
Tile Size		20 @ 500 x 500mm = 5m ²	
Product Weight		4800g/m ²	
General Performance EN 12199		Conforms	
Use Area classification		23, 32, 41	
Reaction to Fire EN 13501-1 IMO MSC 307(88) Annex 1 Part 2 and 5		Class Bfl-S1 Pass	
Marine Usage Marine Equipment Directive 96/98/EC SOLAS 74 US Coast Guard		Conforms Conforms Conforms	
Cigarette Resistance EN 1399		Resistant	
Electrical Behaviour (body voltage) EN 1815		This product does not accumulate static charges above 2kV and is classified as 'antistatic'. For specialist applications where there is a requirement to dissipate the electrostatic charge, see the Polyflor ESD product ranges.	
Slip Resistance EN 13893		Class DS	
Acoustical Impact Noise Reduction EN ISO 10140-3		Rubber floors make a beneficial contribution to impact sound reduction	
Notes		For information regarding handling and installation, adhesives, maintenance, applications and chemical resistance, consult Polyflor.	



January 2017 V004/5

Decoration and shade may vary slightly from the samples shown.
The data presented is correct at the time of printing.
L'information présentée est valable au date d'imprimer.
Sie geben nur einen kleinen Teil des gesamten Dekors und der Farbe wieder.
Los datos presentados eran correctos en el momento de su impresión.



POLYFLOR LTD. - TRANSPORT FLOORING DIVISION
PO BOX 3 RADCLIFFE NEW ROAD WHITEFIELD MANCHESTER M45 7NR UK
TEL: +44 (0)161 767 1111 UK FAX: +44 (0)161 767 2515
E-MAIL: TRANSPORT@POLYFLOR.COM
WWW.VOYAGER.POLYFLOR.COM

James Halstead
FLOORING